



## ProTurfgreen®



**Flexible Polyethylene Pipe for Turf Irrigation**  
**Virgin Black Core with Virgin Turf Green Exterior**

HDPE 3608—ASTM D2239 SE 30288  
 Certified and Listed NSF-Irrigation

Effective January, 2024  
 Supersedes January, 2019

### ASTM D2239

#### SIDR 19 | 80 PSI

Dimensions	1" SKU: PROH0800100	1¼" SKU: PROH0800125
Avg OD (in)	1.169	1.526
ID (in)	1.049	1.380
Min Wall (in)	.060	.073
Wt / Ft (lbs)	.093	.148

#### Print Line

Centennial ProTurf Green® HDPE 80 PSI SIDR 19 SE30288 NSF-IRG PE3608



#### SIDR 15 | 100 PSI

Dimensions	¾" SKU: PROH1000075	1" SKU: PROH1000100	1¼" SKU: PROH1000125
Avg OD (in)	.944	1.189	1.564
ID (in)	.824	1.049	1.380
Min Wall (in)	.060	.070	.092
Wt / Ft (lbs)	.074	.109	.187

#### Print Line

Centennial ProTurf Green® HDPE 100 PSI SIDR 15 SE30288 NSF-IRG PE3608



**Note:** For stocking coil lengths, please see [centennialplastics.com/resources](http://centennialplastics.com/resources)



ISO 9001:2015  
 Certified



Scan here to learn more about ProTurf Irrigation

## ESSENTIAL LINKS *(click link for website or to download file)*

- » **Plastic Pipe Design Calculator**
- » **Weatherability of Thermoplastic Piping Systems**

## CERTIFICATIONS & REFERENCES

- » **ASTM D2239** — Specification covers the testing, marking, in-plant QC, and annual testing requirements for PE pipe intended for non-potable water piping systems and meeting the dimensional requirements of ASTM D2239.
- » **SE 30288** — Polyethylene (PE) Plastic Pipe (SIDR-PR) Based on Controlled Inside Diameter for Non-Potable Water Piping Systems.
- » **PE 3608** — ProTurf™ Black is manufactured from virgin high density polyethylene resin with the cell classification of 345464C per ASTM D3350. The material contains minimum 2% carbon black as a UV inhibitor to accommodate outside storage for at least 18 months.
- » **NSF/ANSI 14** — Plastics Piping System Components and Related Materials establishes the minimum physical, performance and health effects requirements for plastics piping system components and related materials.
- » **ASTM D3350** — Centennial PE3608 meets thermal stability, brittleness temperature and elongation at break requirements as outlined in this specification.
- » **ProTurf Green®** Centennial ProTurf is installed using barbed insert fittings with pinch or screw clamps, push connect, quick connect, and other fitting types. Consult fitting manufacturer for proper installation instructions.
- » **ProTurf Green®** is tested and certified by NSF/ANSI standard 14. This product is marked and listed NSF-IRG.
- » **ProTurf Green®** is certified to NSF/ANSI 372 and conforms with the lead content requirement for the “lead free” plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.
- » **Build America, Buy America (BABA Act)** — We proudly hold a BABA Act certification.

Centennial Plastics follows Proposition 65 – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Our products in their finished form do not require a California Proposition 65 warning label.



[centennialplastics.com](http://centennialplastics.com)



NEBRASKA  
1830 Centennial Ave.  
Hastings, NE 68901

IDAHO  
5150 Treasure Valley Way  
Nampa, ID 83687

[info@centennialplastics.com](mailto:info@centennialplastics.com)  
402-462-2227